



- 7-1/4" Blade capacity
- Powerful 1050W hi-torque motor
- 2-1/4" Max cutting depth
- Bevel tilt from 0-45°
- Auto debris collection system
- Clear visibility panel when cutting
- Ergonomically designed handle
- Safety switch with overload protection



PLYWOOD, MDF, CLADDING, CHIPBOARD, HARD & SOFTWOOD, WOOD WITH NAILS, STEEL PLATE, BOX SECTION (ALL TYPES), ALUMINUM SHEET, I-BEAMS, COPPER PIPE, PLASTIC PIPE, BRICK, CONCRETE, ROOFING BOARDS, CAST IRON PIPE, GALVANNEAL STEEL PIPE, SCAFFOLDING, FENCING (WOOD & STEEL), RAYON BOARD, INSULATED ROOFING, SHEET METAL, T & G JOIST, SIMILAR, ABLE TRAYS, SHEET METAL, SINKING



RAGE CIRCULAR SAW ATTRIBUTES:

- Multipurpose; Cuts Steel, Aluminum, Wood & Plastic.
- Easily cuts wood with nails.
- Produces virtually no sparks, with no coolant required.
- Offers an instantly workable finish.
- Advanced performance; outperforms all other saws.
- RAGE blade cuts up to 165 feet of 1/4" steel*.
- Bevel Tilt 0°-45°.
- High quality construction.

* Evolution Power Tools internal test data.

SUPPLIED WITH:

RAGE Multipurpose TCT Blade, Fence Guide, Carrying Case, Wrench, Safety Goggles, Ear Plugs.

TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz	1050W	Recommended Maximum Duty Cycle	30mins
Amps	10A	Sound Pressure Level (Under Load)	100.8dB(A)
Horse Power	1.75HP	Vibration Level (Under Load)	4.8m/s ²
Box Section (1/8" Wall) 90°	2-1/4"	Tool Weight	15lbs
Box Section (1/8" Wall) 45°	1-3/8"	Tool Dimensions (HxWxL)	11" x 15-1/2" x 17-3/4"
Optimum Thickness Of Cut (Mild Steel Plate)	1/4"	Shipping Weight	24lbs
Cutting Thickness (Wood 90°)	2-1/4"	Shipping Dimensions (HxWxL)	16" x 12" x 22"
Cutting Thickness (Wood 45°)	1-3/8"	UPC#	849713009913
Speed (No Load)	3500 RPM		

BLADE SPECIFICATIONS:

Diameter	7-1/4"	Kerf (Thickness)	.067" (1.7mm)
Bore	20mm	Number of Teeth	20

RAGE 7-1/4" BLADES AVAILABLE:



RAGE Multipurpose TCT Blade. Cuts Steel, Aluminum & Wood.
[as originally supplied with saw]



RAGE Diamond Blade. Cuts Brick, Concrete, Stone Products & More.
[optional accessory]



* For technical specifications, please see blades page 33 at the back of this catalog.