



- 14" Blade capacity
- Powerful 2000W hi-torque motor
- 4-3/4" Max cutting depth
- 7" Max cutting width
- Fast action swivel work clamp
- Angled cuts from 0-45°



STEEL PLATE, BOX SECTION (ALL TYPES), ALUMINUM, I-BEAMS, SOFT WOODS, HARD WOODS, MAN MADE WOODS, TIMBER, COPPER PIPE, PLASTIC PIPES, FLOOR BOARDS, CAST IRON PIPE, STEEL PIPE, SCAFFOLDING, FENCING (WOOD & STEEL), PLASTICS, METAL STUDDING, UNISTRUT & SIMILAR, CABLE TRAYS, CONDUIT



### RAGE2 CHOP SAW ATTRIBUTES:

- Multipurpose; Cuts Steel, Aluminum, Wood & Plastic.
- Doesn't lose depth of cut during use like an abrasive wheel does.
- Faster & cleaner cuts than an abrasive wheel.
- RAGE blade will produce up to 750 cuts per blade in 2" mild steel box section\*.
- No coolant required & produces virtually no sparks.
- High quality construction.
- Offers an instantly workable finish.

\* Evolution Power Tools internal test data.

### SUPPLIED WITH:

RAGE2 Multipurpose TCT Blade, V-Jaw for Pipe Cutting, Hex Wrench, Safety Goggles, Ear Plugs.

### TECHNICAL SPECIFICATIONS:

Motor	120v - 60Hz	2000W	Speed (No Load)	1450 RPM
Amps		18A	Recommended Maximum Duty Cycle	30mins
Horse Power		2.5HP	Sound Pressure Level (Under Load)	112.4dB(A)
Maximum Box Section (1/4" Wall) 90°		4-3/4" x 4-3/4"	Tool Weight	45lbs
Maximum Box Section (1/4" Wall) 45°		3-1/2" x 3-1/2"	Tool Dimensions (HxWxL)	23-1/2" x 11-3/4" x 22-1/2"
Rectangle (1/4" Wall) 90°		4" x 7"	Shipping Weight	61lbs
Rectangle (1/4" Wall) 45°		3" x 4-1/3"	Shipping Dimensions (HxWxL)	18" x 15" x 23"
Round (1/4" Wall) 90°		4-1/8"	UPC#	849713011305
Round (1/4" Wall) 45°		4-1/8"		

### BLADE SPECIFICATIONS:

Diameter	14"	Kerf (Thickness)	.083" (2.2mm)
Bore	1"	Number of Teeth	36

### RAGE2 14" BLADES:



RAGE2 Multipurpose TCT Blade. Cuts Steel, Aluminum & Wood. [ as originally supplied with the saw ]



RAGE2 Diamond Blade. Cuts Brick, Concrete, Stone and much more! [ optional accessory ]

### ADJUSTABLE CHOP SAW STAND:



- Quick release and easily adjustable mounting brackets.
- Sturdy legs fold flat for easy storage and transportation.
- Adjustable work supports complete with rollers.
- Suitable for mounting most makes of chop saws.

HEAVY DUTY

\* For technical specifications, see blades p33 at the back of this catalog.

\* For technical specifications, please call 866-EVO-TOOL or visit [www.evolutionpowertools.com](http://www.evolutionpowertools.com).