

FULL SPECIFICATION SHEETS

STEEL CUTTING SAWS

STEELSAW1 Circular Saw	p2
STEELSAW230 Circular Saw	p3
STEELSAW2 Chop Saw	p4

MAGNETIC DRILLS

EV042 Magnetic Drill	p5
MUSTANG Magnetic Drill	p6
COUGAR Magnetic Drill	p7

STEELSAW1

Industrial Circular Saw



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	1100W
Amps:	15A
Horse Power:	2.25HP
RPM No Load:	3900
Maximum Cutting Reach (1/8" Wall) 90°:	2-1/4"
Maximum Cutting Reach (1/8" Wall) 45°:	1-3/8"
Optimum Thickness Of Cut (Mild Steel Plate):	1/4"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	98.5dB(A)
Vibration Level (Under Load):	2.3m/s ²
Tool Weight:	13lbs
Tool Dimensions (HxWxD):	9-3/8" x 16-15/16" x 10-3/8"
UPC#	849713000026
Part No.:	STEELSAW1

SUPPLIED WITH:

Carrying Case, 7-1/4" Steel Cutting Blade, Wrench, Fence Guide, Side Handle, Spare Carbon Brush Set, Safety Goggles, Ear Plugs, Manual.

BLADE SPECIFICATIONS:

PART NO.: 185BLADEST

Diameter:	7-1/4"
Bore:	20mm
Kerf:	.079" (2.0mm)
Number Of Teeth:	40

STEELSAW230

Industrial Circular Saw



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	1750W
Amps:	15A
Horse Power:	2.35HP
RPM No Load:	2700
Maximum Cutting Reach (1/4" Wall) 90°:	3-1/4"
Maximum Cutting Reach (1/4" Wall) 45°:	2-1/8"
Optimum Thickness Of Cut (Mild Steel Plate):	1/2"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	108.7dB(A)
Vibration Level (Under Load):	3.9m/s ²
Tool Weight:	20lbs
Tool Dimensions (HxWxD):	12-3/8" x 16-3/4" x 12-3/4"
UPC#	849713000101
Part No.:	STEELSAW230

SUPPLIED WITH:

Carrying Case, 9" Steel Cutting Blade, Side Handle, Wrench, Spare Carbon Brush Set, Fence Guide, Safety Goggles, 2 Batteries, Ear Plugs, Manual.

BLADE SPECIFICATIONS:

PART NO.: 230BLADEST

Diameter:	9"
Bore:	1"
Kerf:	.079" (2.0mm)
Number Of Teeth:	48

STEELSAW2

Industrial Chop Saw



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	2200W
Amps:	15A
Horse Power:	3.0HP
RPM No Load:	1450
Max Cut Reach 90° (1/4" Wall - Square):	4-3/4" x 4-3/4"
Max Cut Reach 90° (1/4" Wall - Rectangle):	4" x 7"
Max Cut Reach 90° (1/4" Wall - Round):	5-1/8"
Max Cut Reach 45° (1/4" Wall - Square):	3-1/2" x 3-1/2"
Max Cut Reach 45° (1/4" Wall - Rectangle):	3" x 4-7/16"
Max Cut Reach 45° (1/4" Wall - Round):	4-1/8"
Optimum Thickness Of Cut (Mild Steel Plate):	1/2"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	112.4dB(A)
Tool Weight:	50lbs
Tool Dimensions (HxWxD):	23-1/2" x 13-1/4" x 23-3/4"
UPC#	849713000149
Part No.:	STEELSAW2

SUPPLIED WITH:

14" Steel Cutting Blade, V-Block, Safety Guard, Collection Bin, Spare Carbon Brush Set, Hex Wrench, Safety Goggles, Ear Plugs, Manual.

BLADE SPECIFICATIONS:

PART NO.: 230BLADEST

Diameter:	14"
Bore:	1"
Kerf:	.094" (2.4mm)
Number Of Teeth:	66

EV042

Industrial Magnetic Drill



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	1200W
Amps:	10A
Horse Power:	1.5HP
RPM No Load:	450
Maximum Cutter Diameter:	1-5/8"
Maximum Cutting Depth:	2"
Cutter Shank Diameter:	3/4" Weldon Shank
Stroke Length:	3-5/16"
Magnet Dimensions (HxWxD):	1-1/2" x 3-1/2" x 7"
Magnetic Holding Power :	2850lbs
Rack Raised (HxWxD):	25" x 12-1/2" x 7"
Rack Lowered (HxWxD):	13-1/2" x 12-1/2" x 7"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	90dB(A)
Tool Weight:	24lbs

SUPPLIED WITH:

Oil Coolant System, Hex Keys 2, 3, 4mm, 3 Handles, 1 Shipping Guard, Safety Strap & Chuck Adaptor.

MUSTANG

Industrial Magnetic Drill



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	1200W
Amps:	11A
Horse Power:	1.6HP
RPM No Load:	550
Maximum Cutter Diameter:	1-1/2"
Maximum Cutting Depth:	2"
Cutter Shank Diameter:	3/4" Weldon Shank
Stroke Length:	3-5/16"
Magnet Dimensions (HxWxD):	1-5/6" x 3-1/6" x 6-1/2"
Magnetic Holding Power :	2200lbs
Rack Raised (HxWxD):	18-3/8" x 7-1/2" x 15-3/4"
Rack Lowered (HxWxD):	15-1/8" x 7-1/2" x 15-3/4"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	90dB(A)
Tool Weight:	28lbs
UPC#	849713000262
Part No.:	MUSTANG

SUPPLIED WITH:

Coolant Tank, Quick Release Coolant Pipe, Permanent Safety Guard, Hex Key 2.5mm, Wrench 8mm, 4 Handles, 2 Butterfly Screws, 2 Spring Washers, Safety Chain, Carrying Case, Safety Goggles, Ear Plugs, Manual.

COUGAR

Industrial Magnetic Drill



TECHNICAL SPECIFICATIONS:

Motor 120v ~ 60Hz:	1800W
Amps:	15A
Horse Power:	2.4HP
RPM No Load:	380 - 500
Maximum Cutter Diameter:	2-3/8"
Maximum Cutting Depth:	3"
Cutter Shank Diameter:	3/4" Weldon Shank
Stroke Length:	4-7/8"
Magnet Dimensions (HxWxD):	3-2/3" x 2-1/2" x 7-5/6"
Magnetic Holding Power :	4400lbs
Rack Raised (HxWxD):	24-1/8" x 9" x 11-1/2"
Rack Lowered (HxWxD):	19-7/8" x 9" x 11-1/2"
Recommended Maximum Duty Cycle:	30 mins
Sound Pressure Level (Under Load):	104dB(A)
Tool Weight:	50lbs
UPC#	849713000347
Part No.:	COUGAR

SUPPLIED WITH:

Coolant Tank, Quick Release Coolant Pipe, Permanent Safety Guard, Hex Key 2.5mm, Wrench 8mm, 3 Handles, 2 Butterfly Screws, 2 Spring Washers, Safety Chain, Carrying Case, Safety Goggles, Ear Plugs, Manual.